

# Okoguard®-Okoclear®-TP Type MV-105

## 15 kV Shielded Power Cable

One Okopact® (Compact Stranded)  
Copper Conductor/105°C Rating Wet or Dry  
For Cable Tray Use - Sunlight Resistant



- A Uncoated, Okopact (Compact Stranded) Copper Conductor
- B Strand Screen-Extruded Semiconducting EPR
- C Insulation-Okoguard EPR
- D Insulation Screen-Extruded Semiconducting EPR
- E Shield-Copper Tape
- F Jacket-Okoclear TP (TPPO-LSZH)

### Insulation

Okoguard is Okonite's registered trade name for its exclusive ethylene-propylene rubber (EPR) based, thermosetting compound, whose optimum balance of electrical and physical properties is unequalled in other solid dielectrics. Okoguard insulation, with the distinctive red color and a totally integrated EPR system, provides the optimum balance for long, problem free service.

### Jacket

The Okoclear-TP jacket on this cable is a low smoke, non-halogenated, thermoplastic polyolefin (TPPO) based compound. It provides excellent resistance to mechanical abuse, flame, weathering, most oils, acids and alkalis.

### Applications

Okoguard shielded Okoclear-TP Type MV-105 power cables are recommended for use as feeder circuits, in electric utility generating stations, for distribution circuits, and for feeders or branch circuits in industrial and commercial installations, where a cable with low smoke/zero halogen characteristics is needed.

Type MV cables may be installed in wet or dry locations, indoors or outdoors (exposed to sunlight), in any raceway or underground duct, directly buried if installed in a system with a grounding conductor in close proximity that conforms with NEC Section 315.36 and 250.4(A)(5), or messenger supported in industrial establishments and electric utilities.

May be installed in cable trays where permitted by NEC Section 392 as permitted by NEC Section 315.32(3).

### Specifications

**Conductor:** Uncoated copper compact stranded per ASTM B-496.

**Strand Screen:** Extruded semiconducting EPR strand screen. Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, and UL 1072.

**Insulation:** Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, and UL 1072.

**Insulation Screen:** Extruded semiconducting EPR insulation screen. Meets or exceeds electrical and physical requirements of ICEA S-93-639/NEMA WC74 & S-97-682, AEIC CS8, and UL 1072.

**Shield:** 5 mil bare copper tape helically applied, with 25% minimum overlap.

**Jacket:** Meets or exceeds electrical and physical requirements of ICEA S-93-639 for Type I thermoplastic polyolefin jackets.

UL listed as Type MV-105, sunlight resistant and for use in cable tray in accordance with UL 1072.

### Product Features

- Low smoke/zero halogen jacket.
- Okoguard cables meet or exceed all recognized industry standards (UL, NEMA/ICEA and IEEE).
- Triple tandem extruded, all EPR system.
- 105°C continuous operating temperature.
- 140°C emergency rating.
- 250°C short circuit rating
- Excellent corona resistance.
- Exceptional resistance to "treeing".
- Screens are clean stripping.
- Exceptional resistance to moisture.
- Resistant to most oils, acids, and alkalis.
- UL listed: MV-105, Sunlight Resistant, and Cable Tray Use.
- Passes the UL & IEEE 383-1974 Vertical Tray Flame Test.
- Sizes 500 kcmil and larger pass FT4/IEEE 1202 Vertical Tray Flame Test.

# Okoguard-Okoclear-TP Type MV-105

## 15kV Shielded Power Cable

One Okopact (Compact Stranded)

Copper Conductor/ 105°C Rating

100% and 133% Insulation Level

For Cable Tray Use - Sunlight Resistant



## Product Data Section 2: Sheet 53

Catalog Number (1)	Conductor Size AWG or kcmil		Conductor Size - mm <sup>2</sup>		Approx. Dia. over Insulation (in.)		Approx. Dia. over Screen (in.)		Jacket Thickness - mils		Approx. O.D. - mm		Approx. O.D. - Inches		Approx. Net Weight (lbs./1000')		Approx. Ship Weight (lbs./1000')		Ampacities (2) Conduit in Air		Ampacities (3) Underground		Ampacities (4) Cable Tray		Conduit (5) Size Inches*			
<b>Okoguard Insulation: 175 mils (4.45mm), 100% Insulation Level</b>																												
115-23-3352	1/0	53.5	0.74	0.80	80	2.03	1.05	26.7	790	860	215	215	290	3														
115-23-3353	2/0	67.4	0.78	0.84	80	2.03	1.09	27.7	900	970	255	245	335	3														
115-23-3354	3/0	85.0	0.83	0.89	80	2.03	1.14	29.0	1040	1105	290	275	385	3														
115-23-3355	4/0	107.0	0.87	0.93	80	2.03	1.19	30.2	1200	1310	330	315	445	3½														
115-23-3356	250	127.0	0.93	0.99	80	2.03	1.25	31.8	1365	1450	365	345	495	3½														
115-23-3357	350	177.0	1.02	1.08	80	2.03	1.33	33.8	1720	1850	440	415	610	4														
115-23-3358	500	253.0	1.13	1.19	80	2.03	1.44	36.6	2245	2430	535	500	765	4														
115-23-3359	750	380.0	1.31	1.37	80	2.03	1.62	41.1	3130	3365	655	610	990	5														
115-23-3360	1000	507.0	1.47	1.53	80	2.03	1.78	45.2	4010	4380	755	690	1185	5														

<b>Okoguard Insulation: 220 mils (5.59mm), 133% Insulation Level</b>																												
115-23-3363	1/0	53.5	0.82	0.88	80	2.03	1.13	28.7	870	950	215	215	290	3½														
115-23-3364	2/0	67.4	0.86	0.92	80	2.03	1.17	29.7	985	1065	255	245	335	3½														
115-23-3365	3/0	85.0	0.92	0.98	80	2.03	1.23	31.2	1140	1230	290	275	385	3½														
115-23-3366	4/0	107.0	0.96	1.02	80	2.03	1.27	32.3	1300	1450	330	315	445	3½														
115-23-3367	250	127.0	1.01	1.07	80	2.03	1.33	33.8	1460	1590	365	345	495	4														
115-23-3368	350	177.0	1.10	1.16	80	2.03	1.42	36.1	1830	2015	440	415	610	4														
115-23-3369	500	253.0	1.22	1.28	80	2.03	1.54	39.1	2370	2560	535	500	765	5														
115-23-3370	750	380.0	1.40	1.46	80	2.03	1.71	43.4	3270	3525	655	610	990	5														
115-23-3371	1000	507.0	1.54	1.60	110	2.79	1.92	48.8	4240	4615	755	690	1185	6														
115-23-3372	1250	633.5	1.75	1.81	110	4.33	2.13	54.1	5225	5615	845	770	1350	6														
115-23-3373	1500	760.2	1.88	1.94	110	4.33	2.26	57.4	6105	6665	925	845	1500	8														

Okonite's web site, [www.okonite.com](http://www.okonite.com) contains the most up to date information.

▲ **Authorized Stock Item.** Available from our Customer Service Centers.

### Aluminum Conductors

(1) Aluminum conductors are available on special order.

### Ampacities

(2) Ampacities are in accordance with Table 315.60(C)(7) of the NEC for three single Type MV-105 conductors, or single conductors twisted together (triplexed) and installed in an isolated conduit in air at an ambient temperature of 40°C and a conductor temperature of 105°C.

(3) Ampacities are in accordance with Table 315.60(C)(11) of the NEC for three single conductors or triplexed cable in one underground raceway, three feet deep with a conductor temperature of 105°C, 100% Load Factor, an ambient earth temperature of 20°C and thermal resistance (RHO) of 90.

(4) Ampacities for sale in cable tray are in accordance with the NEC, Section 392.80(B)(2)(2), Table 315.60(C)(3) (copper), for single conductor cables installed in a single layer, in uncovered tray, with a maintained spacing of 1 cable

OD or more at 105°C conductor temperature and 40°C ambient temperature and single point grounding.

Refer to the NEC, IEEE/ICEA-S-135 Power Cable Ampacities, or the Okonite Engineering Data Bulletin for installation in duct banks, multiple point grounded shields, other ambient temperatures, circuit configurations or installation requirements.

(5) Recommended size of rigid or nonmetallic conduit for three conductors based on 40% maximum fill.

\*The jam ratio conduit I.D. to cable O.D. should be checked to avoid possible jamming.